

## Technical Specification



### KEY FEATURES:

- ✓ Bale ejection trolley included as standard
- ✓ Suitable for small volumes of waste material
- ✓ Retainers to prevent material spring back

|                                       |                                                 |
|---------------------------------------|-------------------------------------------------|
| <b>Bale Weights</b>                   | <b>Up to 75kg</b>                               |
| <b>Press Force</b>                    | <b>3.5 tonnes</b>                               |
| <b>Cycle Time</b>                     | <b>24 seconds</b>                               |
| <b>Bale Dimensions</b>                | <b>735 x 700 x 500mm</b>                        |
| <b>Loading Aperture (H x W x D)</b>   | <b>698 x 700 x 500mm</b>                        |
| <b>Approximate Machine Weight</b>     | <b>278kg</b>                                    |
| <b>Noise Level</b>                    | <b>68 decibels</b>                              |
| <b>Power Supply (kW-V-Hz)</b>         | <b>13amp single phase 1.5kW 220-240V – 50Hz</b> |
| <b>Overall Dimensions (H x W x D)</b> | <b>2335 x 1040 x 750mm</b>                      |
| <b>Optional Transport height</b>      | <b>1800mm</b>                                   |

### Extra Options

- Bale ejection
- Galvanised finish
- Insert to crush small cans
- Alternative power supply options – 110V and 16amp 3 phase
- PLC control panel with bale full light